

Power Advanced XP2 Series

300-600 VA Line Interactive UPS

CoolPower
Solutions

- Line Interactive technology
- Stabilization through AVR
- Filtered telephone Plug
- RS-232 and USB Interfaces
- UPS Management Software
- Protection for PC desktop or workstation



Model	FGCPA 600 XP2	FGCPA 800 XP2	FGCPA 1000 XP2	FGCPA 1200 XP2
Advised Protection	1 Desktop + TFT Monitor 15"	1 Desktop + TFT/CRT Monitor 17"	1 Workstation + TFT/CRT Monitor 17"	1 Workstation + TFT/CRT Monitor 20"
Power	300 VA	400 VA	500 VA	600 VA
Technology	Line Interactive with AVR			
Nominal Input Voltage	220/230 V			
Input/Output Range	+20% - 25%			
Input/Output Frequency	50 /60Hz (automatic selection)			
Input Frequency Range	+ -5%			
Nominal Output Voltage	220 / 230 V			
Output Voltage Regulation (Line Mode)	by AVR			
Output Voltage Regulation (Backup Mode)	+ -5%			
Output Inverter Waveform	Modified Siniwave			
Overload Accepted	< 130%			
Transfer Time (typical)	0 ms			
Bypass				
Harmonic Distortion				
Certifications	CE - UL			
Batteries Nominal Voltage	12 Vcc			
Batteries Type	Sealed lead acid battery, free maintenance			
Batteries Number	1			
Batteries Characteristics	12 V 4,5 Ah		12V 7Ah	
Batteries Typical Recharge Time	8 hours			
Batteries Positioning	inside			
Typical Autonomy	6-10 minutes			
Audible Noise (At 1 meter)	< 40 dBA			
Cooling	Natural			
Environmental Specifications	Temperature: 0-40 °C - Humidity: 0-95% (without condensation) - Altitude: max 3.000 m			
Weight	4,5 kg	5,0 kg	5,5 kg	6,0 kg
Dimensions	11,5 x 17,0 x 33,0 cm			
Rs 232 Interface	Included			
USB Interface	Included			
Number Of Output Sockets	3 (IEC Type)			
Filtered Telephone Plug	Included			
Ups Software	UPS software can be uploaded and updated free of charge from www.coolpowersolutions.fi			
Autonomy Extension				

Cool Power Solutions Oy
Keskustie 6
01900 Nurmijärvi
Finland

Tel: +358-9-2906 1990
Fax: +358-9-2906 1991

info@coolpowersolutions.fi
www.coolpowersolutions.fi