SDR240 Series

240 W AC/DC Switching Power Supply – DIN rail

CoolPower Solutions

- High efficiency 94% and low power dissipation
- Protections: Short circuit / Overload / Over voltage / Over temperature
- 150% peak load capability
- Built-in active PFC function, PF>0.93
- UL 508 (industrial control equipment) approved
- Built-in DC OK relay contact



Electrical specifications

Model No.		SDR240-24	SDR240-48
Max Output Wattage (W)		240W (Peak 360W)	240W (Peak 360W)
Input	Voltage	88 ~ 264VAC or 124-370 VDC	
	Frequency (Hz)	47-63 Hz	
	Power Factor (typ)	0,94 / 230VAC	
	Current (typ)	2,6 A (115 VAC) / 1,3 A (230 VAC)	
	Inrush Current (typ)	Cold start 33 A (115 VAC) / 55 A (230 VAC)	
	Leakage Current	<1 mA /240 VAC	
Output	Voltage (V.DC.)	24V	48V
	Voltage Adjustable Range	24 - 28V	48 - 55V
	Voltage Tolerance	±1%	±1%
	Rated Current	10 A (Peak 15A)	5 A (Peak 7,5A)
	Line Regulation	±0,5%	±0,5%
	Load Regulation	±1%	±1%
	Ripple % Noise (max)	50mV$_{p-p}$	50mV$_{p-p}$
	Efficiency (typ)	94%	94%
	Hold-up Time	20 ms / 230 VAC	
	Setup, Rise Time	650 ms, 60 ms / 230 VAC	
Protection	Over Load	Normally works within 110 ~ 150% rated output power for more than 3s and then shut down o/p voltage with auto-recovery	
		>150% rated power, constant current limiting with auto-recovery within 2 seconds and shut down o/p voltage after 2 seconds	
	Over Voltage	29 ~ 33V	56 ~ 65V
		Protection type : Shut down o/p voltage with auto-recovery	
	Over Temperature	95±5°C (TSW : detect on heatsink of power switch)	
		Protection type : Shut down o/p voltage, recovers automatically after temperature goes down	
Function	DC OK Relay contact	Ratings max. 60Vdc/0.3A, 30Vdc/1A, 30Vac/0.5A resistive load	
Environment	Operating Temperature	-25°C…+70°C (with derating)	
	Storage Temperature	-40°C…+85°C, 10 – 95% RH	
	Temperature coefficient	±0.03%/°C (0…50°C)	
	Humidity	20 - 95% RH	
	MTBF	169 300 h @ 25°C (MIL-HDBK-217F)	
Physical	Dimension (W xH x D)	63 x 125,2 x 113,5 mm	
	Weight	1030 g	
	Cooling Method	Free air convection	
Safety	Safety standards	UL508, TUV EN60950-1 approved;(meet EN60204-1)	
	Withstand Voltage	I/P-O/P:3KVAC I/P-FG:2KVAC O/P-FG:0.5KVAC O/P-DC OK:0.5KVAC	
	Isolation Resistance	I/P-O/P, I/P-FG, O/P-FG:>100M Ohms / 500VDC / 25°C / 70% RH	
	EMC Emission	Compliance to EN55011, EN55032 (CISPR32), EN61204-3 Class B, EN61000-3-2,-3	
	EMC Immunity	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024,EN61000-6-2 (EN50082-2), EN61204-3, heavy industry level, criteria A, SEMI F47, GL approved	

CoolPower Solutions

Cool Power Solutions Oy
Vanha Rajamäentie 173
FI-05200 Rajamäki
FINLAND


Tel: +358-9-2906 1990
Fax: +358-9-2906 1991

Email: info@cps.fi
Web: www.cps.fi

SDR240 Series

240 W AC/DC Switching Power Supply – DIN rail

Mechanical Specifications




Terminal Pin No. Assignment (TB1)

Pin No.	Assignment
1	FG ⏚
2	AC/N
3	AC/L


Terminal Pin No. Assignment (TB2)

Pin No.	Assignment
1,2	Relay Contact
3,4	DC OUTPUT +V
5,6	DC OUTPUT -V


Block Diagramm



Derating Curve



Output Derating vs Input Voltage



Cool Power Solutions Oy
Vanha Rajamäentie 173
FI-05200 Rajamäki
FINLAND

Tel: +358-9-2906 1990
Fax: +358-9-2906 1991

Email: info@cps.fi
Web: www.cps.fi