
SZA60O Series

60 W AC/DC Open Frame Switching Power Supply

CoolPower Solutions

KEY FEATURES

- Open Frame Switching Power Supply
- Universal Input: 90-264 VAC
- Single Output
- <0.3W No Load Input Power
- 5 VDC to 48 VDC Output
- 3000 VAC Input to Output Isolation
- Ultra Compact Size: 3.0 x 2.0 x 1.24 Inches
- 3-Years Product Warranty



E199779 LEVEL3

ELECTRICAL SPECIFICATIONS

Model No.		SZA60O-5S	SZA60O-12S	SZA60O-15S	SZA60O-24S	SZA60O-48S
Max Output Wattage (W)		50W	60W			
Input	Voltage	90-264 VAC or 120-370 VDC				
	Frequency (Hz)	47-63 Hz				
	Current (Full load)	2 A max. (115 VAC) / 1 A max. (230 VAC)				
	Inrush Current (Cold Start)	35 A max. (115 VAC) / 70 A max. (230 VAC)				
	Leakage Current	0.75 mA max.				
	No Load Input Power (<230 VAC)	<0.3W				
Output	Voltage (V.DC.)	5V	12V	15V	24V	48V
	Voltage Accuracy	±2%				
	Current (mA) max	10,000	5,000	4,000	2,500	1,250
	Line Regulation (LL-HL) (typ.)	±1%				
	Load Regulation (5-100%) (typ.)	±1%				
	Maximum Capacitive Load	10,000 uF	5,000 uF	4,000 uF	2,000 uF	1,000 uF
	Ripple	<0.2% Vout +40mV max (Vp-p)				
	Noise	<0.5% Vout +50mV max (Vp-p)				
	Efficiency (at 230V)	81%	87%	87%	88%	88%
	Trim	±5%				
	Hold-up Time (>115 VAC)	10 ms min.				
Protection	Over Power Protection	Auto recovery				
	Over Voltage Protection	Zener diode clamp				
	Short Circuit Protection	Auto recovery				
Isolation	Input-Output (V.AC)	3000V				
	Input-FG (V.AC)	1500V				
	Output-FG (V.AC)	500V				
Environment	Operating Temperature	-30°C…+70°C (with derating)				
	Storage Temperature	-50°C…+85°C				
	Temperature coefficient	±0.02%/°C				
	Humidity	95% RH				
	MTBF	>130,000 h @ 25°C (MIL-HDBK-217F)				
	Vibration	10~500Hz, 2G 10min./1cycle, 60min. each along X, Y, Z axes.				
Physical	Dimension (L x W x H)	3.0 x 2.0 x 1.24 Inches (76.3 x 50.6 x 31.5 mm) Tolerance ±0.5 mm				
	Weight	150 g				
	Cooling Method	Free air convection				
Safety	Agency Approvals	CE, UL60950				
EMC	EMI (Conducted & Radiated Emission)	EN 55022 Class B				
	EMS (Noise Immunity)	EN 55024				

1.All specifications valid at normal input voltage, full load and +25°C after warm-up time unless otherwise stated.
2.Ripple & Noise are measured at 20MHz of bandwidth with 0.1UF & 47UF parallel capacitor.

Cool Power Solutions Oy
Vanha Rajamäentie 173
FI-05200 Rajamäki
FINLAND

Tel: +358-9-2906 1990
Fax: +358-9-2906 1991


Email: info@cps.fi
Web: www.cps.fi

SZA60O Series

60 W AC/DC Open Frame Switching Power Supply


CoolPower Solutions


MECHANICAL DIMENSION (Top View)




PIN#	SINGLE
1	AC IN (N)
2	AC IN (L)
3	FG
4	+DC OUT
5	-DC OUT

DERATING





BLOCK DIAGRAM



Cool Power Solutions Oy
Vanha Rajamäentie 173
FI-05200 Rajamäki
FINLAND

Tel: +358-9-2906 1990
Fax: +358-9-2906 1991

Email: info@cps.fi
Web: www.cps.fi