

- IEC/EN/UL 62368-1 3rd Edition
- Universal Input Range 100-240VAC
- 2 pin Euro Input
- Single Regulated 24W Output with Low Ripple Noise
- Over Voltage, Over Current and Short Circuit Protection
- Efficiency ErP Stage 2, DoE Level VI and CoC Tier 2
- Safety Agency Requirements and EMI/EMS Certified



Electrical specifications

Input	Voltage	100-240 VAC
	Frequency	50-60 Hz
	Current (Full load)	580 mA max.
	Protection	Internal Primary Current Fuse
	Configuration	EU: 2 pin Euro Input. UK, US, AU & CN versions available.
Output	Output Power	24 W
	Voltage (VDC)	See table below
	Current (A) max.	See table below
	Load regulation	± 5.0% typical
	Ripple & Noise	≤ 2% Vp-p @ Full Load
	Transient Response	0,5 ms with 50% Load Change
	Start-up Time	< 3 000 ms
	Hold-up Time	≥ 10 ms @ Full Load
	Rise Time	< 50 ms
	Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection
Electrical	Topology	Switching Flyback
	Dielectric Withstand	3 000 VAC Primary - Secondary
	Leakage Current	< 0,25 mA
	Efficiency	ErP Stage 2, DoE Level VI, CoC Tier 2
	EMC Standards	EN55032
		EN61000-3-2,3
EN55035		
MTBF	300 000 h Calculated Hours at 25°C by Telcordia SR-332	
Environment	Operating Temperature	-20°C...+40°C (+60°C with derating 50%)
	Storage Temperature	-20°C...+80°C
	Operating Altitude	2 000 m
	Relative Humidity	Operating: 20...80% RH (No-condensing)
	Cooling	Natural Convection Cooling
Mechanical	Dimension (L x W x H)	72 x 34 x 90 mm (EU)
	Weight	154 g
	DC cord	22AWG / 20AWG / 18AWG / 16AWG, Without Ferrite core (optional)
Safety	Safety Approvals	EU: CB / CE / GS / LPS UK: CB / UKCA / LPS US: CB / UL / cUL / FCC / PSE / BSMI / LPS AU: CB / RCM / LPS CN: CB / CCC / LPS

CPS Series

24 W AC/DC Plug-in Switching Power Supply

CoolPower
Solutions

Description

The CPS-24W series of AC/DC switching mode power supplies provide 24 Watts of continuous output power and is well-suited for a variety of applications. All supplies include Euro plug-in. Other output voltages, DC plugs and input connectors available.

Models

Model no	Output voltage	Max output current	Max output power	DC Plug
CPS-05040EU/3630+	5,0 VDC	4,0 A	20,00 W	2.1/5.5 mm +center
CPS-05935EU/3630+	5,9 VDC	3,5 A	20,65 W	2.1/5.5 mm +center
CPS-05940EU/3630+	5,9 VDC	4,0 A	23,60 W	2.1/5.5 mm +center
CPS-07030EU/3630+	7,0 VDC	3,0 A	21,00 W	2.1/5.5 mm +center
CPS-07530EU/3630+	7,5 VDC	3,0 A	22,50 W	2.1/5.5 mm +center
CPS-09025EU/3630+	9,0 VDC	2,5 A	22,50 W	2.1/5.5 mm +center
CPS-12020EU/3630+	12 VDC	2,0 A	24,00 W	2.1/5.5 mm +center
CPS-15016EU/3630+	15 VDC	1,6 A	24,00 W	2.1/5.5 mm +center
CPS-24010EU/3630+	24 VDC	1,0 A	24,00 W	2.1/5.5 mm +center
CPS-48005EU/3630+	48 VDC	0,5 A	24,00 W	2.1/5.5 mm +center

CoolPower
Solutions